

ASSISTANT COMMISSIONER FOR PATENTS
 Washington, D.C. 20231

FORM PTO-1082
 Case Docket No. 51270-245579
 Date: February 10, 1999
 Express Mail Label No. EL073550247US

Dear Sir:

Transmitted herewith for filing is the reissue patent application of
 Inventor(s): **Mikio Ogusu, Kazunobu Fujiwara, and Kei Tanaka**
 For: **MUSICAL INFORMATION RECORDING AND REPRODUCING TECHNIQU916E FOR
 USE WITH A RECORDING MEDIUM HAVING A UTOC AREA**

Enclosed are:

- ☒ 9 Sheet(s) of drawings (☒ informal)
- ☒ Request For Transfer of Drawings
- ☒ Reissue Application by the Assignee, Assent of Assignee to Reissue, And Offer to Surrender Original Patent
- ☒ Power of Attorney by Assignee
- ☒ Declaration of Mikio Ogusu, Kazunobu Fujiwara, and Kei Tanaka for Reissue Application
- ☒ IDS enclosed. ☒ with references.

135 U.S. PTO
09/24/99
 02/10/99


CALCULATION OF FEES							
ITEM		NO. OF CLAIMS FILED MINUS BASE*		NO. OF CLAIMS OVER BASE	X SM/LG ENTITY FEE	\$ AMOUNT	\$ FEE
A	TOTAL CLAIMS FEE	5	- 20* =	0	X \$9 or X \$18	\$0	
B	INDEPENDENT CLAIMS FEE**	5	- 3* =	2	X \$39 or X 78	\$156	
C	SUBTOTAL - ADDITIONAL CLAIMS FEE (ADD FINAL COLUMN IN LINES A + B)						\$156
D	MULTIPLE-DEPENDENT CLAIMS FEE				SMALL ENTITY FEE = \$130 LARGE ENTITY FEE = \$260		\$
E	BASIC FEE*				SMALL ENTITY FEE = \$380 LARGE ENTITY FEE = \$760		\$760
F	TOTAL FILING FEE (ADD TOTALS FOR LINES C, D, AND E)						\$916
F	ASSIGNMENT RECORDING FEE					\$ 40	\$
	**1 LIST INDEPENDENT CLAIMS 1-5						

- Please charge my Deposit Account No. 16-1805 the amount of \$0
 - ☒ A check in the amount of \$916
 - A check in the amount of \$
- A copy of this letter is enclosed.**
- to cover the filing fee is enclosed.
- to cover Assignment Recordation fee is enclosed.

- X The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 16-1805.
- X Any additional filing fees required under 37 CFR 1.16.
- X Any patent application processing fees under 37 CFR 1.17.

- The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 16-1805.
- Any patent application processing fees under 37 CFR 1.17.
- The issue fee set in 37 CFR 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR 1.311(b).
- Any filing fees under 37 CFR 1.16 for presentation of extra claims.

Respectfully submitted,



Roger R. Wise
Reg. No. 31,204

Date: February 10, 1999

PILLSBURY MADISON & SUTRO LLP
725 South Figueroa Street, Suite 1200
Los Angeles, CA 90017-5443
Telephone: (213) 488-7100
Facsimile: (213) 629-1033

660720 "363

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Reissue application of:)	Prior Art Unit: 2516
)	Prior Examiner: M. EDUN
Mikio Ogusu, Kazunobu Fujiwara, and)	
Kei Tanaka)	
)	
Reissue Application Serial No: Unassigned)	
Reissue Application Filing Date:)	
)	
)	
Original Patent No. 5,602,811)	
Issued: February 11, 1997)	
)	
For: MUSICAL INFORMATION RECORDING)	
AND REPRODUCING TECHNIQUE FOR)	
USE WITH A RECORDING MEDIUM)	
HAVING A UTOC AREA)	
_____)	

**REISSUE APPLICATION BY THE ASSIGNEE,
ASSENT OF ASSIGNEE TO REISSUE,
AND OFFER TO SURRENDER ORIGINAL PATENT**

Commissioner of Patents and Trademarks
Washington, D.C. 20231

Dear Sir:

YAMAHA CORPORATION possesses sole interest in the above-identified reissue application by an assignment previously submitted in the application for the original patent. YAMAHA CORPORATION has reviewed the executed assignment and to the best of its knowledge and belief, title to the above identified invention and reissue application resides in YAMAHA CORPORATION. The evidentiary document supporting this knowledge and belief, as required by 37 C.F.R. § 3.73(b), is the executed

Assignment document. This Assignment was recorded at Reel 7616, Frames 0744-45, as indicated by the NOTICE OF RECORDATION OF ASSIGNMENT dated August 2, 1995 in the application for the original patent. The assignee of the accompanying reissue application hereby applies for the reissue of Letters Patent No. 5,602,811 entitled MUSICAL INFORMATION RECORDING AND REPRODUCING MEDIUM HAVING A UTOC AREA granted to Mikio Ogusu, Kazunobu Fujiwara, and Kei Tanaka on February 11, 1997 of which YAMAHA CORPORATION is now the sole owner by assignment, and hereby offers to surrender said Letters Patent and assents to the accompanying reissue application.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed by me to be true; and further that these statements were made with the knowledge that willful false statements and the like are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Filed herewith is a Request for Transfer of Drawings from the original patent for use in this application.

DATED: February 2, 1999

YAMAHA CORPORATION


Name: Hirokazu Kato
Title: Director
for YAMAHA CORPORATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Reissue application of:)
)
Mikio Ogusu, Kazunobu Fujiwara, and)
Kei Tanaka)
)
Reissue Application Serial No: Unassigned)
Reissue Application Filing Date:)
)
)
Original Patent No. 5,602,811)
Issued: February 11, 1997)
)
For: MUSICAL INFORMATION RECORDING)
AND REPRODUCING TECHNIQUE FOR)
USE WITH A RECORDING MEDIUM)
HAVING A UTOC AREA)
)

POWER OF ATTORNEY BY ASSIGNEE
AND EXCLUSION OF INVENTOR UNDER 37 C.F.R. § 3.71

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

The undersigned is a representative authorized to sign on behalf of the assignee of the entire interest of the above-identified application, **YAMAHA CORPORATION**, and hereby appoints:

Paul N. Kokulis, Reg. No. 16,773; Raymond F. Lippitt, Reg. No. 17,519; G. Lloyd Knight, Reg. No. 17,698; George M. Sirilla, Reg. No. 18,221; Carl G. Love, Reg. No. 18,781; Kevin E. Joyce, Reg. No. 20,508; Edgar H. Martin, Reg. No. 20,534; David W. Brinkman, Reg. No. 20,817; Jay M. Finkelstein, Reg. No. 21,082; William K. West, Jr., Reg. No. 22,057; Edward M. Prince, Reg. No. 22,429; G. Paul Edgell, Reg. No. 24,238; Donald J. Bird, Reg. No. 25,323; Peter W. Gowdey, Reg. No. 25,872; W. Warren Taltavull, Reg. No. 26,647; Richard H. Zaitlen, Reg. No. 27,248; Glenn J. Perry, Reg. No. 28,458; Dale S. Lazar, Reg. No. 28,872; Kendrew H. Colton, Reg. No. 30,368; Mark G. Paulson, Reg. No. 30,793; Barry L. Grossman, Reg. No. 30,844; John P. Moran, Reg. No. 30,906; Paul E. White, Jr., Reg. No. 31,097; Roger R. Wise, Reg. No. 31,204; Stephen C. Glazier, Reg. No. 31,361; Paul F. McQuade, Reg. No. 31,542; Jeffrey A. Simenauer, Reg. No. 31,933; Michelle N. Lester, Reg. No. 32,331; David A. Jakopin, Reg. No. 32,995; Timothy J. Klima, Reg. No. 34,852; Lynn E. Eccleston, Reg. No. 35,861; Paul G. Nagy, Reg. No. 37,896; Peter J. Gluck, Reg. No. 38,022; Steven W. Smyrski, Reg. No. 38,312; Richard K. Yoon, Reg. No. 42,247; Eric S. Chen, Reg. No. P-43,542; Vivian S. Shin, Reg. No. P-43,919 and

**REISSUE APPLICATION FOR
UNITED STATES PATENT
IN THE NAME OF**

MIKIO OGUSU, KAZUNOBU FUJIWARA, AND KEI TANAKA

ASSIGNED TO

YAMAHA CORPORATION

FOR

**MUSICAL INFORMATION RECORDING AND REPRODUCING TECHNIQUE
FOR USE WITH A RECORDING MEDIUM HAVING A UTOC AREA**

**ORIGINAL U.S. PATENT NO. 5,602,811
ISSUED: FEBRUARY 11, 1997**

DOCKET NO. 51270-245579

**PILLSBURY MADISON & SUTRO LLP
725 South Figueroa Street
Suite 1200
Los Angeles, California 90017
Telephone (213) 488-7100
Facsimile (213) 629-1033**

**Express Mail No.
EL073550247US**

5602811 5624260

MUSICAL INFORMATION RECORDING AND REPRODUCING TECHNIQUE FOR USE WITH A RECORDING MEDIUM HAVING A UTOC AREA

TITLE OF THE INVENTION

Musical Information Recording and Reproducing Technique for Use with a Recording Medium having a UTOC Area

BACKGROUND OF THE INVENTION

The present invention relates generally to a musical information recording and reproducing technique for use with a recording medium having a UTOC (User's-table-of-contents) area.

More particularly, the present invention relates to musical information recording and reproducing devices and a musical information recording medium which permit display of a measure being currently reproduced and selective quick access to the starting point of any desired measure.

The present invention also relates to a multichannel mixing recorder for recording input musical signals onto optionally selected channels and mixing the musical signals recorded on the plural channels, and more particularly to such a multichannel mixing recorder which allows a user to readily verify the assignment of various performance parts to individual channels to thereby achieve smooth multiplex recording and editing.

On recording media such as a CD (Compact Disk), MD (Mini Disk) and DCC (Digital Compact Cassette), there are recorded musical information of music pieces and address information associated therewith. Thus, during reproduction from the media, the address of every point of the music piece being currently reproduced can be displayed in a successive manner. Additionally, information indicative of the respective starting points (heads) of the individual music pieces is also recorded on the media as TOC (Table of Contents) information so that the starting point of any desired music piece can be immediately accessed on the basis of this TOC information.

In musical education, or other cases where a recorded musical instrument performance is reproduced for practices on the instrument, it may be very convenient if a player is informed of which measure in the score is being currently reproduced by a reproducing device. It may be even more convenient if the starting point of a specific measure can be immediately accessed by mere designation of a unique number allocated to that measure. However, none of the conventionally known CD, MD and DCC playing devices were capable of achieving such measure-by-measure display and starting point access, although they could permit display of the varying addresses (passage of time) and starting point access for each of the music pieces recorded. Consequently, the known CD, MD and DCC playing devices were not so convenient for purposes like musical education and musical instrument practices.

Further, in the known CD, MD or DCC playing devices, multichannel recording is done by first performing rhythm parts to record the performed rhythm parts onto optionally designated individual channels ("initial recording"), then performing one or more other parts, while reproducing the recorded rhythm parts, to record the other parts onto other channels ("overdubbing"), and finally reproducing and mixing together the recorded performance parts of all the

0924295-5524260

channels so as to ultimately output the resultant mixed performance parts through two (right and left) channels ("mixdown"). Where relatively many performance parts are involved, the multichannel recording is done by first overdubbing and mixing some of the performance parts, then temporarily transferring the resultant mixed performance parts onto an empty channel ("ping-pong recording") so as to record other performance parts onto the channels that have become empty due to the ping-pong recording, and finally mixing down the recorded performance parts of all the channels.

However, with the conventionally known CD, MD or DCC playing device, the multichannel recording involves preparing a planning sheet where there are written, for each of the steps, the assignment of the performance parts to the individual channels and various settings such as effectors to be applied to the performance parts. The operator (i.e., person in charge) handles the channel assignment etc. in accordance with the planning sheet. However, whenever it was desired to ascertain, during recording, which parts have so far been assigned to which channels, the operator had to refer to the planning sheet.

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide musical information recording and reproducing devices and a musical information recording medium which permit display of a measure number being currently reproduced and quick access to the starting point of any desired measure.

It is another object of the present invention to provide a multichannel recorder which allows a user to readily verify the assignment of performance parts to individual channels without having to referring to a planning sheet so as to achieve smooth multiplex recording and editing of musical information.

In order to accomplish the first object, the present invention provides a recording device for recording musical information of a music piece onto a recording medium having address information previously recorded thereon, which device comprises a tempo designation section for designating a tempo of a music piece to be recorded, a meter designation section for designating meter of the music piece, a rhythm generation section for generating, in light or sound form, a rhythm corresponding to the tempo and meter designated by the tempo and meter designation sections, a start timing instruction section for instructing timing to start performance of the music piece, an input section for inputting musical information of the music piece, a music piece recording section for recording, onto the recording medium, the musical information of the music piece input by the input section, a start address retrieval section for retrieving, as a start address of the music piece, the address information read out from the recording medium when the timing to start performance of the music piece is instructed by the instruction section, and a tempo, meter and start address recording section for recording, onto a predetermined recording area of the recording medium, information indicative of the tempo and meter designated by the tempo and meter designation sections and the start address retrieved by the retrieval section.

According to the recording device thus arranged, a specific rhythm is generated by the rhythm generation section in response to designation of a desired tempo and meter of a music piece to be recorded. Performance of a musical instrument or the like is started at specific timing according

to the generated rhythm, and the performance (performed sound) information resulting from the performance is recorded onto the recording medium by the music piece recording section. The address on the recording medium read out when the performance of the music piece is started is retrieved, as a start address of the music piece, by the retrieval section. After completion of the musical information recording, the retrieved start address of the music piece is recorded onto the predetermined recording area (corresponding to the UTOC area in the later-described embodiments) of the medium along with information indicative of the designated tempo and meter. With this arrangement, display of a measure number being currently reproduced and quick access to the starting point of any desired measure can be achieved by an appropriate reproducing device reading the information indicative of the music piece start address, tempo and meter and calculating the measure number, start address of the desired measure etc. on the basis of the read information.

The present invention also provides a reproducing device for reproducing recorded information from a recording medium having musical information of a music piece recorded thereon along with associated address information and also having other information indicative of a tempo, meter and start address of the music piece recorded on a predetermined recording area thereof, which device comprises a reading section for, prior to reproduction of the music piece, reading the information indicative of the tempo, meter and start address from the predetermined recording area of the recording medium, a reproduction section for reproducing the musical information of the music piece along with the associated address information, a measure number calculation section for calculating a measure number n being currently reproduced, by performing an arithmetic operation of $n = \text{INT}\{(T_a - T_s)/N \cdot t\} + 1$, where T_s represents in seconds the start address of the music piece read by the reading section, T_a represents in seconds an address being currently reproduced, N represents the meter read by the reading section, t represents in seconds the tempo read by the reading section and $\text{INT}\{(T_a - T_s)/N \cdot t\}$ represents an integer part of $(T_a - T_s)/N \cdot t$, and a measure number display section for displaying the measure number calculated by the calculation section.

According to the reproducing device thus arranged, a measure number n can be displayed by reading the information indicative of the music piece start address, tempo and meter from the predetermined recording area (corresponding to the UTOC area in the later-described embodiments) of the medium and calculating the measure number n corresponding to the current reproduction address.

The present invention also provides a reproducing device for reproducing recorded information from a recording medium having musical information of a music piece recorded thereon along with associated address information and also having other information indicative of a tempo, meter and start address of the music piece recorded on a predetermined recording area thereof, which device comprises a reading section for, prior to reproduction of the musical information of the music piece, reading the information indicative of the tempo, meter and start address of the music piece from the predetermined recording area, a reproduction section for reproducing the musical information of the music piece along with the associated address information, a measure number designation section for designating a measure number in the music piece, a measure start address calculation section for calculating a start address T_a of the measure number designated by the mea-

sure designation section, by performing an arithmetic operation of $Ta = Ts + (n-1) \cdot N \cdot t$, where Ts represents in seconds the start address of the music piece read by the reading section, n represents the measure number designated by the designation section, N represents the meter read by the reading section and t represents in seconds the tempo read by the reading section, and a measure start address search section for searching, on the recording medium, for the measure start address calculated by the calculation section so that reproduction of the music piece is started at the calculated measure start address.

According to the reproducing device thus arranged, by reading the information indicative of the music piece start address, tempo and meter of the music piece from the predetermined recording area (corresponding to the UTOC area in the later-described embodiments) of the medium and in response to designation of a measure number n whose starting point is to be accessed, the start address Ta of the designated measure number n is accurately calculated and thereby quick access to the starting point of the measure can be achieved for precise, selective reproduction of the measure.

The present invention also provides a recording medium which has musical information of a music piece recorded thereon along with corresponding address information and also has other information indicative of a tempo, meter and start address of the music piece recorded on a predetermined recording area thereof. With this recording medium, display of a measure number being currently reproduced and quick access to the starting point of any desired measure can be achieved by an appropriate reproducing device reading the information indicative of the music piece start address, tempo and meter and calculating the measure number, start address of the desired measure etc. on the basis of the read information.

The present invention mentioned above should be found very convenient because of the features to permit display of a measure number being currently reproduced and quick access to the starting point of any desired measure.

Further, in order to accomplish the second object, the present invention provides a multichannel recorder for recording musical information onto a recording medium, which comprises a mixing section for supplying externally input musical signals to recording channel inputs of channels optionally designated from among plural channels of the recording medium, a part information input operation section for inputting part information indicative of performance parts of the externally input musical signals, a recording and reproduction control section for recording, onto a table-of-contents information recording area of the recording medium, the part information input by the operation section as part information for the designated channels, and reproducing the part information from the table-of-contents information recording area, and a display section for displaying the part information for each of the channels reproduced from the table-of-contents information recording area of the recording medium. According to the multichannel recorder thus arranged, part information indicative of performance parts assigned to the individual channels is recorded on the table-of contents recording area (corresponding to the UTOC area in the later-described embodiments). By reading out the part information from the table-of contents recording area and displaying the read-out part information, the user is allowed to readily verify the assignment of various performance parts to the individual channels without a need to refer to a planning sheet, to thereby achieve smooth multiplex recording and editing of musical information.

Typically, the mixing section is constructed to mix the musical signals reproduced from plural channels optionally designated for reproduction from among the channels of the recording medium, so as to supply the mixed musical signals to a recording channel input of another channel optionally designated for recording from among of the channels, and wherein the recording and reproduction control section synthesizes the part information of the channels optionally designated for reproduction among the part information reproduced from the table-of-contents area of the recording medium, so as to automatically record the synthesized part information as part information for the other channel designated for recording. It is allowed to automatically create part information for the recording channel by use of the part information already recorded for the reproducing channels. This will reduce the necessary time and labor for entering the performance parts.

For better understanding of the above and other features of the present invention, the preferred embodiments of the invention will be described in detail below with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

FIG. 1 is a block diagram illustrating the general hardware structure of an MD recording/reproducing device in accordance with an embodiment of the present invention;

FIG. 2 is a diagram explanatory of an example of tempo/meter/music start address information generated as UTOC information;

FIG. 3 is a diagram explanatory of a recording operation of the MD recording and reproducing device;

FIG. 4 is a diagram explanatory of a measure search operation performed during reproduction;

FIG. 5 is a system block diagram illustrating another embodiment where the principle of the present invention is applied to a four-channel MD recorder;

FIG. 6 is a sectional view of an MD showing the format of the disk;

FIG. 7 is a diagram illustrating an example of part information recorded on the UTOC area of the MD in FIG. 2;

FIG. 8A is a block diagram showing the connecting condition of a mixer in a first step of multichannel recording performed by the four-channel MD recorder of FIG. 5;

FIG. 8B is a diagram showing part information recorded on the UTOC area in the first step of the multichannel recording;

FIG. 9A is a block diagram showing the connecting condition of the mixer in a second step of the multichannel recording;

FIG. 9B is a diagram showing part information recorded on the UTOC area in the second step of the multichannel recording;

FIG. 10A is a block diagram showing the connecting condition of the mixer in a third step of the multichannel recording;

FIG. 10B diagram showing part information recorded on the UTOC area in the third step of the multichannel recording;

FIG. 11A is a block diagram the connection condition of the mixer in a fourth step of the multichannel recording, and

FIG. 11B diagram showing part information recorded on the UTOC area in the fourth step of the multichannel recording.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

With reference to FIGS. 1 to 4, a description will hereinafter be made on an embodiment where the principle of the present invention is applied to an MD recording/reproducing device and an MD.

In FIG. 1, the MD 10 is driven to rotate by a spindle motor 12. Above and below the MD 10 are provided a recording head (magnetic head) 14 and an optical pickup 16 in opposed relation to each other. The recording head 14 and optical pickup 16 are mechanically interconnected for movement along the radius of the MD 10 via a feed motor 18.

In recording, each musical signal input through an input terminal 22 is converted by an A/D converter 24 into digital representation and then converted by a sound compression/expansion section 27 into compressed form. The thus-compressed signal is temporarily stored into a memory (shock-proof memory) 31 via a memory controller 29 and then subjected to an EFM (Eight-to-fourteen Modulation) process performed via an EFM/ACIRC (Advanced Cross Interleave Reed-Solomon)-encoder/decoder 33. A head drive section 35 modulates a head drive signal with the EFM signal to drive the recording head 14. The optical pickup 16 irradiates a recording laser beam of predetermined power onto the recording surface of the disk 10 which is opposite to the recording head 14, to thereby effect recording based on magnetic field modulation. In reproduction, on the other hand, the optical pickup 16 irradiates a reproducing laser beam of lower power to read the recorded information from the disk 10.

In reproduction, each RF signal output from the optical pickup 16 is amplified via an RF amplifier 19 and then EFM-demodulated by the EFM/ACIRC-encoder/decoder 33. The thus-demodulated program signal (musical signal) is temporarily stored into the memory 31 under the control of the memory controller 29 and is then read out to be expanded by the sound compression/expansion section 27. The expanded signal from the compression/expansion section 27 is converted by a D/A converter 36 into analog representation and then output via an output terminal 41.

Position (address) information, which is recorded in advance on pre-grooves in the disk 10, is decoded via an address decoder 37 for utilization by a system controller 45. A servo control circuit 43, by use of the output signal from the optical pickup 16, performs focusing, tracking and feed control of the optical pickup 16 as well as rotation control of the spindle motor 12. The rotation control of the spindle motor 12 is performed in such a manner that wobble signal can be detected at a predetermined frequency.

During recording and reproduction, the system controller 45 controls the entire operation of the MD recording/reproducing device 11. A display 47 displays a position, music piece number, measure number etc. being recorded or reproduced by the device 11. A key switch section 49 outputs a signal to instruct recording, reproduction, temporary stop, stop or the like, in response to the user's operation on any of key switches contained in the key switch section 49.

A tempo designation operator 50 is an operating member, such as ten keys or a knob, for the user to designate a desired tempo of a music piece to be recorded. A meter designation operator 52 comprises an operating member, such as a knob or switch, for the user to designate a desired time or meter (such as triple or quadruple meter) of a music piece to be recorded. The meter designation operator 52 may comprise operating members for designating any of rhythm types like waltz, march etc., rather than the above-mentioned operating member for directly designating the meter.

The system controller 45 receives the designated tempo and meter so as to actuate a metronome 54 to generate a rhythm (corresponding to the tempo and meter). The metronome 54 is provided with LEDs 56 and speaker 58 so as to light any of the LEDs in correspondence to the designated tempo and audibly generate the corresponding rhythm via the speaker 58.

A music piece number designation operator 62 and a measure number designation operator 64 comprise operating members, such as ten keys, for designating a music piece number and a measure number, respectively, during reproduction. Further, a music piece start timing instruction operator 60 includes an operating member for instructing a start (beginning of the first measure) of a music piece to be recorded, and it outputs a timing signal (trigger signal) when the user activates a foot switch or the like at predetermined performance start timing according to the rhythm generated by the metronome 54. Alternatively, the timing signal may be automatically output by detecting the first performance action on a musical instrument (performance start)—in such a case, the performing section such as a keyboard of the musical instrument itself functions as the music piece start timing instruction operator 60. A memory 61 is provided for storing the designated tempo and meter, address information corresponding to the music piece start timing, and UTOC (User's-table-of-contents) information read out from the disk 10.

Next, a description will be made on an example of the recording and reproducing control performed by the system controller 45.

(1) Recording Control

A desired tempo and meter of a music piece to be recorded are designated via the tempo and meter designation operators 50 and 52, respectively, and the designated tempo and meter are stored into the memory 61. Thus, the metronome 54 generates a rhythm corresponding to the designated tempo and meter in sound and light. Then, after having placed the disk 10 in the recording condition, the player or user activates the timing instruction operator 60 at specific timing corresponding to the rhythm generated from the generator 54 by listening to or viewing the generated rhythm, so as to initiate a performance (this activation of the operator 60 is unnecessary where it is done automatically). Once a music piece start timing instruction is given from the operator 60, the system controller 45 retrieves the address information read out from the MD 10 to store it into the memory 61 as a music piece start address.

FIG. 2 is a diagram explanatory of exemplary relationships between the rhythm generated by the metronome 54, performance and music piece start timing instruction where the performance is started in four-four (4/4) meter. During the performance, the rhythm generation and control of recording rate on the MD 10 are effected in synchronism with each other on the basis of a same system clock.

Upon termination of the performance, the tempo information, meter information and address information of the music piece start position are read out from the memory 61, generated as UTOC information corresponding to the tempo, meter and music piece start address information, and then recorded onto the UTOC area of the MD 10. FIG. 3 shows an example of the UTOC information thus recorded. According to the embodiment, the UTOC information may include the track (music piece) number on the assumption that a plurality of music pieces are recorded onto the same disk 10. The tempo and meter information, instead of being individually recorded, may be recorded as the product of their respective values.

(2) Reproducing Control

Once the disk 10 is set in the MD recording/reproducing device 11, the UTOC information stored in the UTOC area of the disk 10 is automatically loaded into the memory 61. Then, in response to the player's designation of a music piece number and predetermined reproducing operation, the start address of the designated music piece number is read out from the memory 61, and the position indicated by the read-out address is searched for or retrieved so that the music piece is reproduced from its very beginning.

While the music piece is reproduced, the passage of time is displayed on the basis of simultaneously read-out address information. Also, the system controller 45 carries out the following arithmetic operation so as to display a measure number being currently reproduced in a successive manner:

$$n = \text{INT}\{(Ta - Ts)/N \cdot t\} + 1 \quad (1)$$

where Ta represents in seconds the address being currently reproduced, Ts the music piece start address in seconds, N the meter, t the tempo in seconds, and $\text{INT}\{(Ta - Ts)/N \cdot t\}$ the integer part of $(Ta - Ts)/N \cdot t$. In response to the player's designation of music piece and measure numbers and predetermined operation, the system controller 45 calculates the start address Ta of the designated measure number of the designated music piece number on the basis of the following equation:

$$Ta = Ts + (n - 1) \cdot N \cdot t \quad (2)$$

Then, the system controller 45 searches for the calculated address Ta so that reproduction starts at the beginning of the designated measure. FIG. 4 shows the search operation performed when measure number n is designated.

Although the embodiment has been described above in connection with a case where the principle of the present invention is applied to an MD recording/reproducing device, the invention may of course be applied to other kinds of recording/reproducing device which use other recording media such as different type optical disks, optical magnetic disks, magnetic tapes and magnetic disks.

According to the invention having the above-described features, display of a measure number being currently reproduced and quick access to the starting point of any desired measure can be achieved by just reading the information indicative of the music the piece start address, tempo and meter and calculating the measure number, start address of the desired measure etc. on the basis of the read information. Consequently, the invention will be very conveniently used in musical education and practices on a musical instrument.

Next, with reference to FIGS. 5 to 11, another embodiment of the present invention will be described in relation to a case where the principle of the invention is applied to a four-channel MD recorder 1.

FIG. 6 shows the disk format of an MD 10 for use with the recorder 1. A lead-in area 2 is disposed along inner-most circumference of the disk 10, and a lead-out area 4 is disposed along the outer-most circumference of the disk 10. Between the lead-in and lead-out area 2 and 4 is provided a recordable area 6 available for recording by the user. In the inner-most region of the recordable area 6, there is provided a UTOC area (User's-table-of-contents recording area) 8 where part information is recorded as will be later described, while in the outer-most region, there is provided a program area 9 for storing program information (in this embodiment, musical information) for four channels.

In FIG. 7, there is shown an example of the part information formation recorded on the UTOC area 8 of the disk

10. Here, in order to deal with a possible increase in the number of performance parts due to repetition of "ping-pong recording", 12-performance part names are recorded, for each of the four channels CH1-CH4, in alphabetical abbreviations (e.g., drum part is recorded as "DR", vocal part as "VOC" and keyboard part as "KEY").

FIG. 5 shows the systematic arrangement of the four-channel MD recorder 1 which performs multichannel recording by use of the above-mentioned disk 10. Similarly to the embodiment of FIG. 1, the MD 10 is driven to rotate by a spindle motor 12. Above and below the MD 10 are provided a recording head (magnetic head) 14 and an optical pickup 16 in opposed relation to each other. The recording head 14 and optical pickup 16 are mechanically interconnected for movement along the radius of the MD 10 via a feed motor 18.

To line inputs Li1 to Li4 are input respective musical signals from outside the MD recorder 1. A mixer (mixing means) 20 receives the musical signals supplied through the lines Li1 to Li4, and musical signals reproduced from the MD 10 and supplied through channel outputs CHo1 to CHo4. Then, in response to the user's external operation for setting the contents of desired mixing, channel assignment, etc., the mixer 20 provides any of the received musical signals singly or in mixed form to channel inputs CHi1 to CHi4, or to line outputs Lo1 to Lo4 and monitor output Mo. The mixer 20 also provides mixdown output to the right and left channels "R"CH and "L"CH. The mixer 20 also provides a system controller 48 with mixing information that indicates various settings for desired mixing based on the user's external operation, such as the contents of initial recording, overdubbing, ping-pong recording, and mixdown).

In recording, each musical signal supplied from the mixer 20 to the channel inputs CHi1 to CHi4 is converted by a corresponding A/D converter 72-75 into digital representation and then converted by a sound compression section 28 into compressed form. The thus-compressed signal is temporarily stored into a memory (shock-proof memory) 32 via a memory controller 30 and then read out to be subjected to an EFM (Eight-to-fourteen Modulation) process performed via an EFM/ACIRC-encoder/decoder 34. A head drive section 35 modulates a head drive signal with the EFM signal to drive the magnetic recording head 14. The optical pickup 16 irradiates a recording laser beam of predetermined power onto the recording surface of the disk 10 which is opposite to the recording head 14, to thereby effect recording based on magnetic field modulation.

In reproduction, on the other hand, readout from the MD 10 of the recorded information is executed by actuating the optical pickup 16 to irradiate a reproducing laser beam onto the disk 10. Each RF signal that is then output from the optical pickup 16 is amplified via an RF amplifier 38 and then EFM-demodulated by the EFM/ACIRC-encoder/decoder 34. The thus-demodulated program signal (musical signal) is temporarily stored into the memory 32 under the control of the memory controller 30 and is then read out for signal expansion by a sound expansion section 40. The expanded signal from the expansion section 40 is converted by a corresponding D/A converter 82-85 into analog representation and then provided to the mixer 20 via the corresponding channel output CHo1-CHo4.

As earlier mentioned in connection with the embodiment of FIG. 1, position (address) information, which is recorded in advance on pre-grooves in the disk 10, is decoded via an address decoder 46 for utilization by the system controller 48. A servo control circuit 90, by use of the output signal

from the optical pickup 16, performs focusing, tracking and feed control of the optical pickup 16 as well as rotation control of the spindle motor 12. The rotation control of the spindle motor 12 is performed in such a manner that wobble signal is detected at a predetermined frequency.

The system controller 48 controls the entire operation of the MD recorder 1. Further, as a part information recording/reproducing control means, the system controller 48 controls recording and reproduction of the part information onto and from the UTOC area of the MD 10. A key switch section 92 includes keys for use by the user to instruct recording, reproduction, stop etc., and also includes alphanumeric keys etc., as a part information input operator means, for use by the user to enter a desired performance part name. A display 94 displays addresses (passage of time) and also displays the part information for each of the channels reproduced from the UTOC area of the MD 10 (the display 94 may display the part information only when the user so instructs by operating a predetermined key).

Now, an example of the multichannel recording performed by the four-channel MD recorder 1 of FIG. 5 will be described step by step, with reference to FIGS. 8 to 11, of which FIGS. 8A, 9A, 10A and 11A show the connecting conditions of the mixer 20 in the respective steps of the multichannel recording and FIGS. 8B, 9B, 10B and 11B show the contents of part information recorded in the corresponding steps in the UTOC area of the MD 10.

(1) Step 1: Sound or musical signals for the drum part are recorded onto channel 1 (FIGS. 8A and 8B)

- 1) The microphone output for the drum part is connected to line input Li1.
- 2) The connecting condition of the mixer 20 is set in such a manner to interconnect line input Li1 and channel input CHi1.
- 3) From mixing information supplied by the mixer 20, the system controller 48 detects that line input Li1 and channel input CHi1 have been interconnected.
- 4) The system controller 48 causes the display 94 to make a display which prompts the user to enter a desired performance part name.
- 5) The user uses the key switch section 92 to enter a performance part name "DR", for example.
- 6) The entered part name is temporarily stored into a predetermined region of the memory 32.
- 7) A recording key in the key switch section 92 is activated by the user to initiate sound recording.
- 8) After completion of the recording, the system controller 48 retrieves the part information from the memory 32 and records the retrieved information onto the UTOC area of the MD 10 (FIG. 8B).

(2) Step 2: Sound signals for the bass guitar part are recorded onto channel 2 while channel 1 is monitored (FIGS. 9A and 9B).

- 1) The information on the UTOC area of the MD 10 is reproduced so as to store into the memory 32 the part information having so far been recorded on the UTOC area.
- 2) Sound recording is performed in a similar manner to step 1, and in response to the user's entry of, for example, "BG" as a performance part name for channel 2, part information recording onto the UTOC area of the MD 10 is effected as shown in FIG. 9B.

(3) Step 3: Sound signals for the rhythm guitar part are recorded onto channel 3 while channels 1 and 2 are monitored (FIGS. 10A and 10B).

- 1) The information on the UTOC area of the MD 10 is reproduced so as to store into the memory 32 the part information having so far been recorded on the UTOC area.
- 2) Sound recording is performed in a similar manner to steps 1 and 2, and response to the user's entry of, for example, "RG" as a performance part name for channel 3, part information recording onto the UTOC area of the MD 10 is effected as shown in FIG. 10B.
- (4) Step 4: The sound signals recorded on channels 1, 2 and 3 are mixed and then ping-pong recorded onto channel 4 (FIGS. 11A and 11B).
 - 1) The information on the UTOC area of the MD 10 is reproduced so as to store into the memory 32 the part information having so far been recorded on the UTOC area.
 - 2) The connecting condition of the mixer 20 is set in such manner to mix channel outputs CHo1, CHo2 and CHo3 and then provide the mixed result to channel input CHi4.
 - 3) From mixing information supplied by the mixer 20, the system controller 48 detects the settings in the mixer 20.
 - 4) The recording key in the key switch section 92 is activated by the user to initiate sound recording. But, this time, the user is not prompted to enter a desired performance part because there is no performance part to be newly performed. Then, the system controller 48 automatically additively synthesizes "DR", "BG" and "RG" and adds the synthesized names, as performance part names for channel 4, to the part information of the memory 32.
 - 5) After completion of the recording, the system controller 48 retrieves the part information from the memory 32 to thereby update the recording on the UTOC area of the MD 10 (FIG. 11B).

Where a new part performance input from outside the recorder 1 is to be simultaneously mixed in the ping-pong recording, the user is prompted to enter the name of the new performance part. Further, where plural music pieces are recorded onto a single MD 10, the part information may be managed independently for each music piece.

While performance part names are entered by use of alphanumeric keys in the embodiment of FIG. 5, there may be provided key switches corresponding to the individual performance parts so that any desired performance part may be entered at one touch on selected one of plural key switches that are provided in corresponding relation to the individual performance part names. Further, while the embodiment has been described as recording the part information onto the UTOC area after the sound recording in each step, the part information may alternatively be recorded before the sound recording in each step. Furthermore, although the embodiment has been described as reading out the part information from the MD 10 whenever the step is initiated, it is not necessary to do so if the part information recorded up to the last step is caused to remain stored in the memory 32. Moreover, while the embodiment has been described above as applied to an MD recorder, the present invention is also applicable to multichannel recorders using other kinds of recording media.

According to the embodiment of FIG. 5 thus arranged, by just reading out the part information from the UTOC area and displaying the read-out part information, the user is allowed to readily verify the assignment of various performance parts to the individual channels without a need to

refer to a planning sheet, to thereby achieve smooth multiplex recording and editing of musical information.

What is claimed is:

1. A recording device for recording musical information of a music piece onto a recording medium having address information previously recorded thereon said device comprising:

tempo designation means for designating a tempo of a music piece to be recorded;

meter designation means for designating meter of said music piece;

rhythm generation means for generating, in light or sound, a rhythm corresponding to the tempo and meter designated by said tempo and meter designation means;

start timing instruction means for instructing timing to start performance of said music piece;

input means for inputting musical information of said music piece;

music piece recording means for recording, onto the recording medium, the musical information of said music piece input by said input means;

start address retrieval means for retrieving, as a start address of said music piece, the address information read out from the recording medium when the timing to start performance of said music piece is instructed by said instruction means, and

tempo, meter and start address recording means for recording, onto a predetermined recording area of the recording medium, information indicative of the tempo and meter designated by said tempo and meter designation means and the start address retrieved by said retrieval means.

2. A reproducing device for reproducing recorded information from a recording medium having musical information of a music piece recorded thereon along with associated address information and also having other information indicative of a tempo, meter and start address of the music piece recorded on a predetermined recording area thereof, said device comprising:

reading means for, prior to reproduction of the music piece, reading the information indicative of the tempo, meter and start address from the predetermined recording area of the recording medium;

reproduction means for reproducing the musical information of the music piece along with the associated address information;

measure number calculation means for calculating a measure number n being currently reproduced, by performing an arithmetic operation of

$$n = \text{INT}\{(T_a - T_s)/N \cdot t\} + 1$$

where T_s represents in seconds the start address of the music piece read by said reading means, T_a represents in seconds an address being currently reproduced, N represents the meter read by said reading means, t represents in seconds the tempo read by said reading means and $\text{INT}\{(T_a - T_s)/N \cdot t\}$ represents an integer part of $(T_a - T_s)/N \cdot t$, and

measure number display means for displaying the measure number calculated by said calculation means.

3. A reproducing device for reproducing recorded information from a recording medium having musical information of a music piece recorded thereon along with associated address information and also having other information indicative of a tempo, meter and start address of the music

piece recorded on a predetermined recording area thereof, said device comprising:

reading means for, prior to reproduction of the musical information of the music piece, reading the information indicative of the tempo, meter and start address of the music piece from the predetermined recording area;

reproduction means for reproducing the musical information of the music piece along with the associated address information;

measure number designation means for designating a measure number in the music piece;

measure start address calculation means for calculating a start address Ta of the measure number designated by said measure designation means, by performing an arithmetic operation of

$$T_a = T_s + (n-1) \cdot N \cdot t$$

where T_s represents in seconds the start address of the music piece read by said reading means, n represents the measure number designated by said designation means, N represents the meter read by said reading means and t represents in seconds the tempo read by said reading means, and

measure start address search means for searching, on the recording medium, for the measure start address calculated by said calculation means so that reproduction of the music piece is started at the calculated measure start address.

650720 " 55324260

4. A reproducing device for reproducing recorded information from a recording medium having musical information of a music piece recorded thereon along with associated address information and also having other information indicative of a tempo, meter and start address of the music piece recorded on a predetermined recording area thereof, said device comprising:

reading means for, prior to reproduction of the music piece, reading the information indicative of the tempo, meter and start address from the predetermined recording area of the recording medium;

reproducing means for reproducing the musical information of the music piece along with the associated address information;

measure number calculation means for calculating a measure number corresponding to the address information being currently reproduced in accordance with the address information along with which the music information is currently reproduced and also with the start address, tempo, and meter read by said reading means; and

measure number display means for displaying the measure number calculated by said calculation means.

5. A reproducing device for reproducing recorded information from a recording medium having musical information of a music piece recorded thereon along with associated address information and also having other information indicative of a tempo, meter and start address of the music piece recorded on a predetermined recording area thereof, said device comprising:

reading means for, prior to reproduction of the musical information of the music piece, reading the information indicative of the tempo, meter and start address of the music piece from the predetermined recording area;

measure number designation means for designating a measure number in the music piece;

measure start address calculation means for calculating a start address of the measure number designated by said measure number designation means in accordance with the measure number designated by said measure number designation means and also with the start address, tempo and meter of the music piece read by said reading means;

measure start address search means for searching, on the recording medium, for the measure start address calculated by said calculation means; and

reproduction means for reproducing the music information of the music piece, starting from the measure start address detected by said measure start address search means.

[57]

ABSTRACT

There is generated a rhythm corresponding to a designated tempo and meter of a music piece to be recorded. Performance of a musical instrument is started at specific timing according to the generated rhythm, and the musical information resulting from the performance is recorded onto an MD (Mini Disk). The address on the MD read out when the performance of the music piece is started is retrieved as a start address of the music piece. After the recording, the retrieved start address is recorded onto the UTOC (User's-table-of-contents) area of the disk along with the designated tempo and meter. By reading out the start address, tempo and meter to calculate a measure number and start address of a desired measure on the basis of the read out information, display of a measure number being currently reproduced and quick access to the starting point of any desired measure can be achieved. In applications where plural channels are involved, part information indicative of performance parts assigned and recorded on the individual recording channels is also recorded onto the UTOC area. When necessary, the part information is visually displayed. In ping-pong recording, performance parts to be mixed are additively synthesized on the basis of the recorded part information and then recorded onto the UTOC area as part information for a channel where the mixed output is to be recorded.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Reissue application of:) Prior Art Unit: 2516
) Prior Examiner: M. EDUN
Mikio Ogusu, Kazunobu Fujiwara, and)
Kei Tanaka)
)
Reissue Application Serial No: Unassigned)
Reissue Application Filing Date:)
)
)
Original Patent No. 5,602,811)
Issued: February 11, 1997)
)
For: MUSICAL INFORMATION RECORDING)
AND REPRODUCING TECHNIQUE FOR)
USE WITH A RECORDING MEDIUM)
HAVING A UTOC AREA)
_____)


REQUEST FOR TRANSFER OF DRAWINGS

Commissioner of Patents and Trademarks
Washington, D.C. 20231

Dear Sir:

The undersigned, as attorney for the applicants and the assignee, YAMAHA CORPORATION, respectfully requests that the drawings from application serial No. 08/510,377, filed August 2, 1995, now U.S. Patent No. 5,602,811, issued February 11, 1997, be transferred for use in this reissue application.

DATED: February 10, 1999



ROGER R. WISE, Reg. No. 31,204
Attorney for Applicants
YAMAHA CORPORATION




FIG. 1




FIG. 2

TRACK NO.	MUSIC PIECE START ADDRESS	TEMPO	METER
k	Ts	t	N

FIG. 3


[illegible]

FIG. 4




FIG. 5




FIG. 6

CH1	PART 1	PART 2	PART 3	PART 4
	PART 5	PART 6	PART 7	PART 8
	PART 9	PART 10	PART 11	PART 12
	PART 13	PART 14	PART 15	PART 16
CH2				
		↑		
CH3				
		↑		
CH4				
		↑		

FIG. 7




FIG. 8A

PART
INFORMATION
OF UTOC AREA

CH1	DR			
CH2				
CH3				
CH4				

FIG. 8B




FIG. 9A

PART
INFORMATION
OF UTOC AREA

CH1	DR			
CH2	BG			
CH3				
CH4				

FIG. 9B




FIG. 10A

PART
INFORMATION
OF UTOC AREA

CH1	DR			
CH2	BG			
CH3	RG			
CH4				

FIG. 10B




FIG. 11A

PART
INFORMATION
OF UTOC AREA

CH1	DR			
CH2	BG			
CH3	RG			
CH4	DR	BG	RG	

FIG. 11B

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Reissue application of:) Prior Art Unit: 2516
) Prior Examiner: M. EDUN
Mikio Ogusu, Kazunobu Fujiwara, and)
Kei Tanaka)
)
Reissue Application Serial No: Unassigned)
Reissue Application Filing Date:)
)
)
Original Patent No. 5,602,811)
Issued: February 11, 1997)
)
For: MUSICAL INFORMATION RECORDING)
AND REPRODUCING TECHNIQUE FOR)
USE WITH A RECORDING MEDIUM)
HAVING A UTOC AREA)
_____)

DECLARATION OF MIKIO OGUSU, KAZUNOBU FUJIWARA, AND KEI TANAKA
FOR REISSUE APPLICATION
UNDER 37 C.F.R § 1.175

Commissioner of Patents and Trademarks
Washington, D.C. 20231

Dear Sir:

We, MIKIO OGUSU, KAZUNOBU FUJIWARA, and KEI TANAKA, the
undersigned, declare:

1. That we are citizens of Japan and that our residence and post office
addresses are as stated below our signatures to this Declaration.
2. That we are named inventors of U.S. Patent No. 5,602,811 entitled
MUSICAL INFORMATION RECORDING AND REPRODUCING TECHNIQUE FOR

USE WITH A RECORDING MEDIUM HAVING A UTOC AREA (the '811 patent), which issued on February 11, 1997 from U.S. application serial No. 08/510,377, filed August 2, 1995.

3. That we verily believe that we are the original, first, and joint inventors of the invention entitled MUSICAL INFORMATION RECORDING AND REPRODUCING TECHNIQUE FOR USE WITH A RECORDING MEDIUM HAVING A UTOC AREA, described and claimed in the above-identified '811 patent and in the specification thereof, and for which invention we solicit a reissue patent; that we have reviewed and understand the contents of said patent and said specification, including the original claims and the new claims added in the reissue application; that we believe we are the first, original and joint inventors of the subject matter that is claimed and for which a patent is sought; that we do not know and do not believe the same was ever known or used in the United States of America before our invention thereof, or patented or described in any printed publication in any country before our invention thereof, or more than one year prior to the application for said patent; that same was not in public use or on sale in the United States of America more than one year prior to the application for said patent; that the invention has not been patented or made the subject of an inventor's certificate issued before the date of application for said patent in any country foreign to the United States of America on an application filed by ourselves or by our legal representatives or assigns more than twelve months prior to the application for said patent; and that we acknowledge our duty to disclose information of which we are aware and that is material to the examination of this application.

4. That we verily believe original U.S. Patent No. 5,602,811 to be, through

error and without any deceptive intent, wholly or partly inoperative or invalid by reason of our claiming, in certain respects, less than we had a right to claim in the original patent. Specifically, we now believe that we had the right to claim in the original patent not only claims 1-3, which are present in the issued patent, but also new claims 4 and 5 included in this reissue application. For example, we now believe that we had the right to claim in the original patent a claim, in the form of claim 2 of the original patent, not including the specific limitation of performing an arithmetic operation in the measure number calculation means. Furthermore, we now believe that we had the right to claim in the original patent a claim, in the form of claim 3 of the original patent, not including the specific limitation of performing an arithmetic operation in the measure start address calculation means.

5. That we verily believe that we are entitled to make these new claims 4 and 5 as they are fully supported by the original disclosure of our U.S. application that resulted in the '811 patent, and that new claims 4 and 5 add no new matter.

6. That we verily believe that all errors which are being corrected in the present reissue application up to the time of filing of this declaration arose without any deceptive intention.

7. We acknowledge the duty to disclose to the U.S. Patent Office all information known to be material to patentability as defined in 37 C.F.R. § 1.56.

8. We hereby declare that all statements made herein of our own knowledge are true and that all statements made on information and belief are believed by us to be true; and further that these statements were made with the knowledge that willful false statements and the like are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

DATED: January 28, 1999

Mikio Ogusu
MIKIO OGUSU

RESIDENCE: Hamamatsu
JAPAN

POST OFFICE: c/o YAMAHA
CORPORATION
10-1, Nakazawa-cho
Hamamatsu-shi,
Shizuoka-ken
JAPAN

DATED: January 28, 1999

Kazunobu Fujiwara
KAZUNOBU FUJIWARA

RESIDENCE: Hamamatsu
JAPAN

POST OFFICE: c/o YAMAHA
CORPORATION
10-1, Nakazawa-cho
Hamamatsu-shi,
Shizuoka-ken
JAPAN

DATED: Jan. 27, 1999

Kei Tanaka
KEI TANAKA

RESIDENCE: Hamamatsu
JAPAN

POST OFFICE: c/o YAMAHA
CORPORATION
10-1, Nakazawa-cho
Hamamatsu-shi,
Shizuoka-ken
JAPAN

all of the firm of PILLSBURY MADISON & SUTRO LLP as its attorneys to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith.

YAMAHA CORPORATION, is the owner of the entire right, title and interest in and to U.S. Patent No. 5,602,811 (and therefore this reissue application) by virtue of an Assignment recorded at Reel 7616, Frames 0744-45 in the records of the U.S. Patent Office. **YAMAHA CORPORATION**, per 37 C.F.R. §3.73(b), certifies that the evidentiary documents with respect to its ownership have been reviewed and that to the best of the undersign's knowledge and belief, title is in the assignee seeking this action.

Please direct all telephone calls to **Roger R. Wise** at (213) 488-7100 and all correspondence relative to said application to the following address:

Roger R. Wise
PILLSBURY MADISON & SUTRO LLP
725 South Figueroa Street, Suite 1200
Los Angeles, CA 90017-5443

ASSIGNEE: **YAMAHA CORPORATION**

Date: February 2, 1999

Signature: 

Title:

Director

Address:

10-1, Nakazawa-cho, Hamamatsu-shi
Shizuoka-ken, 430-8650 JAPAN

550720 5524260